



G125WCU-3A-T4F



Model	G125WCU-3A-T4F		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	151	100	125
@ 240V-3Ø, 0.8PF, 60Hz	301	100	125
@ 208V-3Ø, 0.8PF, 60Hz	336	97	121
@ 240V-1Ø, 1.0PF, 60Hz	360	86.5	86.5
@ 120V-1Ø, 1.0PF, 60Hz	360 × 2	86.5	86.5
@ 400V-3Ø, 0.8PF, 50Hz	152	84	105
Voltage Configuration	3-Position Switch		
Frequency Capability	50Hz/60Hz Switchable		
ENGINE			
Engine Make / Model	Cummins QSB5-G11		
Displacement (L)	4.5		
Number of Cylinders	4		
Power Output @ 1800RPM - HP (kWm)	153 (114)		
Emissions Tier Level	Tier 4 Final		
Aftertreatment Technology	DOC / SCR		
Usable Fuel Tank Capacity - Gal (L)	176.5 (668)		
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	24.4 (92.4)		
Runtime @ 100% Load - Hr	24.5		
DIMENSIONS WITH RUNNING GEAR			
Length - in (mm)	171 (4343)		
Width - in (mm)	72.5 (1841)		
Height - in (mm)	91.0 (2311)		
Weight (Ready to Run) - lb (kg)	6950 (3152)		
Sound Level @ 23 ft (7m) and 100%	68		



AUTHORIZED DEALER



FOR SALES & SERVICE
1-800-287-1538 • tdmgo.com