



G190WCU-3A-T4F



Model	G190WCU-3A-T4F		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	218	145	181
@ 240V-3Ø, 0.8PF, 60Hz	434	145	181
@ 208V-3Ø, 0.8PF, 60Hz	501	145	181
@ 240V-1Ø, 1.0PF, 60Hz	458	110	110
@ 120V-1Ø, 1.0PF, 60Hz	458 × 2	110	110
@ 400V-3Ø, 0.8PF, 50Hz	238	132	165
Voltage Configuration	3-Position Switch		
Frequency Capability	50Hz/60Hz Switchable		
ENGINE			
Engine Make / Model	Cummins QSB7-G8		
Displacement (L)	6.7		
Number of Cylinders	6		
Power Output @ 1800RPM - HP (kWm)	219 (163)		
Emissions Tier Level	Tier 4 Final		
Aftertreatment Technology	DOC / SCR		
Usable Fuel Tank Capacity - Gal (L)	330 (1249)		
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	24.4 (92.4)		
Runtime @ 100% Load - Hr	31.7		
DIMENSIONS WITH RUNNING GEAR			
Length - in (mm)	224 (5689)		
Width - in (mm)	83.2 (2114)		
Height - in (mm)	102.9 (2615)		
Weight (Ready to Run) - lb (kg)	11377 (5172)		
Sound Level @ 23 ft (7m) and 100%	69		



AUTHORIZED DEALER



FOR SALES & SERVICE

1-800-287-1538 • tdmgo.com