



| Model | G240WCU-3B-T4F | | |
|------------------------|----------------------|-----|-----|
| PRIME POWER RATING | AMPS | KW | KVA |
| @ 480V-3Ø, 0.8PF, 60Hz | 283 | 188 | 235 |
| @ 240V-3Ø, 0.8PF, 60Hz | 566 | 188 | 235 |
| @ 208V-3Ø, 0.8PF, 60Hz | 608 | 175 | 219 |
| @ 240V-1Ø, 1.0PF, 60Hz | 567 | 136 | 136 |
| @ 120V-1Ø, 1.0PF, 60Hz | 567 × 2 | 136 | 136 |
| @ 400V-3Ø, 0.8PF, 50Hz | 289 | 160 | 200 |
| Voltage Configuration | Link Board Panel | | |
| Frequency Capability | 50Hz/60Hz Switchable | | |

| ENGINE | | |
|-----------------------------------------------|-----------------|--|
| Engine Make / Model | Cummins QSB7-G8 | |
| Displacement (L) | 6.7 | |
| Number of Cylinders | 6 | |
| Power Output @ 1800RPM - HP (kWm) | 282 (210) | |
| Emissions Tier Level | Tier 4 Final | |
| Aftertreatment Technology | DOC / SCR | |
| Usable Fuel Tank Capacity - Gal (L) | 330 (1249) | |
| Diesel Exhaust Fluid (DEF) Capacity - Gal (L) | 24.4 (92.4) | |
| Runtime @ 100% Load - Hr | 24.4 | |
| DIMENSIONS WITH RUNNING GEAR | | |
| Length - in (mm) | 224 (5689) | |
| Width - in (mm) | 83.2 (2114) | |
| Height - in (mm) | 102.9 (2615) | |
| Weight (Ready to Run) - lb (kg) | 11377 (5172) | |
| Sound Level @ 23 ft (7m) and 100% | 69 | |





DoosanPortablePower.com | 800.633.5206

© 2018 Doosan Portable Power. All rights reserved.