



Model	G25WDO-3A-T4F		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	30	20	25
@ 240V-3Ø, 0.8PF, 60Hz	60	20	25
@ 208V-3Ø, 0.8PF, 60Hz	61	17	22
@ 240V-1Ø, 1.0PF, 60Hz	69	16.5	16.5
@ 120V-1Ø, 1.0PF, 60Hz	69 × 2	16.5	16.5
@ 400V-3Ø, 0.8PF, 50Hz	29	16	20
Voltage Configuration	3-Position Switch		
Frequency Capability	50Hz/60Hz Switchable		

ENGINE	
Engine Make / Model	Doosan D18
Displacement (L)	1.794
Number of Cylinders	3
Power Output @ 1800RPM - HP (kWm)	33.5 (25)
Emissions Tier Level	Tier 4 Final
Aftertreatment Technology	DOC
Usable Fuel Tank Capacity - Gal (L)	46.7 (177)
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	N/A
Runtime @ 100% Load - Hr	25.9
DIMENSIONS WITH RUNNING GEAR	





DoosanPortablePower.com | 800.633.5206

Length - in (mm)

Width - in (mm)

Height - in (mm)

Weight (Ready to Run) - lb (kg)

Sound Level @ 23 ft (7m) and 100%

© 2018 Doosan Portable Power. All rights reserved.

130.5 (3315)

72.8 (1850)

76.6 (1946)

3140 (1424)

63