



Model	G325WCU-3B-T4F		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	401	267	334
@ 240V-3Ø, 0.8PF, 60Hz	803	267	334
@ 208V-3Ø, 0.8PF, 60Hz	877	253	316
@ 240V-1Ø, 1.0PF, 60Hz	821	197	197
@ 120V-1Ø, 1.0PF, 60Hz	821 × 2	197	197
@ 400V-3Ø, 0.8PF, 50Hz	404	224	280
Voltage Configuration	Link Board Panel		
Frequency Capability	50Hz/60Hz Switchable		

ENGINE		
Engine Make / Model	Cummins QSL9-G9	
Displacement (L)	8.9	
Number of Cylinders	6	
Power Output @ 1800RPM - HP (kWm)	393 (293)	
Emissions Tier Level	Tier 4 Final	
Aftertreatment Technology	DOC / SCR	
Usable Fuel Tank Capacity - Gal (L)	460 (1741)	
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	24.4 (92.4)	
Runtime @ 100% Load - Hr	24.1	
DIMENSIONS WITH RUNNING GEAR		
Length - in (mm)	240 (6098)	
Width - in (mm)	83 (2109)	
Height - in (mm)	113 (2870)	
Weight (Ready to Run) - lb (kg)	14032 (6378)	
Sound Level @ 23 ft (7m) and 100%	76	





DoosanPortablePower.com | 800.633.5206

© 2018 Doosan Portable Power. All rights reserved.