



Model	G40WDO-3A-T4F		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	47	31	39
@ 240V-3Ø, 0.8PF, 60Hz	93	31	39
@ 208V-3Ø, 0.8PF, 60Hz	106	31	39
@ 240V-1Ø, 1.0PF, 60Hz	134	32	32
@ 120V-1Ø, 1.0PF, 60Hz	134 × 2	32	32
@ 400V-3Ø, 0.8PF, 50Hz	45	25	31
Voltage Configuration	3-Position Switch		
Frequency Capability	50Hz/60Hz Switchable		

Frequency Capability	50Hz/60Hz Switchable	
ENGINE		
Engine Make / Model	Doosan D24	
Displacement (L)	2.392	
Number of Cylinders	4	
Power Output @ 1800RPM - HP (kWm)	48.8 (36)	
Emissions Tier Level	Tier 4 Final	
Aftertreatment Technology	DOC	
Usable Fuel Tank Capacity - Gal (L)	110 (416)	
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	N/A	
Runtime @ 100% Load - Hr	44.9	
DIMENSIONS WITH RUNNING GEAR		
Length - in (mm)	130.5 (3315)	
Width - in (mm)	72.8 (1850)	
Height - in (mm)	78.4 (1992)	
Weight (Ready to Run) - lb (kg)	3870 (1755)	





DoosanPortablePower.com | 800.633.5206

Sound Level @ 23 ft (7m) and 100%

© 2018 Doosan Portable Power. All rights reserved.

64