



Model	G400WCU-3B-T4F		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	484	322	402
@ 240V-3Ø, 0.8PF, 60Hz	967	322	402
@ 208V-3Ø, 0.8PF, 60Hz	1116	322	402
@ 240V-1Ø, 1.0PF, 60Hz	900	216	216
@ 120V-1Ø, 1.0PF, 60Hz	900 × 2	216	216
@ 400V-3Ø, 0.8PF, 50Hz	559	310	387
Voltage Configuration	Link Board Panel		
Frequency Capability	50Hz/60Hz Switchable		

ENGINE		
Engine Make / Model	Cummins QSG12	
Displacement (L)	11.8	
Number of Cylinders	6	
Power Output @ 1800RPM - HP (kWm)	475 (354)	
Emissions Tier Level	Tier 4 Final	
Aftertreatment Technology	DOC / DPF / SCR	
Usable Fuel Tank Capacity - Gal (L)	470 (1780)	
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	46 (174)	
Runtime @ 100% Load - Hr	20.2	
DIMENSIONS WITH RUNNING GEAR		
Length - in (mm)	241 (6121)	
Width - in (mm)	83 (2109)	
Height - in (mm)	115 (2921)	
Weight (Ready to Run) - lb (kg)	15450 (7022)	
Sound Level @ 23 ft (7m) and 100%	79	





DoosanPortablePower.com | 800.633.5206

© 2018 Doosan Portable Power. All rights reserved.