



Model	G70WDO-3A-T4F		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	84	56	70
@ 240V-3Ø, 0.8PF, 60Hz	168	56	70
@ 208V-3Ø, 0.8PF, 60Hz	190	55	68
@ 240V-1Ø, 1.0PF, 60Hz	209	50	50
@ 120V-1Ø, 1.0PF, 60Hz	209 × 2	50	50
@ 400V-3Ø, 0.8PF, 50Hz	89	50	62
Voltage Configuration	3-Position Switch		
Frequency Capability	50Hz/60Hz Switchable		

ENGINE	
Engine Make / Model	Doosan D34
Displacement (L)	3.409
Number of Cylinders	4
Power Output @ 1800RPM - HP (kWm)	85.8 (64)
Emissions Tier Level	Tier 4 Final
Aftertreatment Technology	DOC / SCR
Usable Fuel Tank Capacity - Gal (L)	110 (416)
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	5.1 (19.3)
Runtime @ 100% Load - Hr	25
DIMENSIONS WITH RUNNING GEAR	
Length - in (mm)	163.8 (4161)
Width - in (mm)	71.3 (1810)
Height - in (mm)	93.3 (2371)
Weight (Ready to Run) - lb (kg)	5550 (2518)
Sound Level @ 23 ft (7m) and 100%	64





DoosanPortablePower.com | 800.633.5206

© 2018 Doosan Portable Power. All rights reserved.