



Model		NG160			
PRIME POWER RATING		AMPS	KW	KVA	
@ 480V-3Ø, 0.8PF, 60Hz	Natural Gas	201	134	167	
@ 400V-3Ø, 0.8PF, 50Hz	Natural Gas	213	118	147	
@ 480V-3Ø, 0.8PF, 60Hz	Propane	146	97	121	
@ 400V-3Ø, 0.8PF, 50Hz	Propane	148	82	102	
Voltage Configuration		Dec	Dedicated Voltage		
Frequency Capability		50Hz/60Hz Switchable			
ENGINE					
Engine Make / Model		PS	PSI 8.1 L Turbo		
Displacement (L)		8.1			
Number of Cylinders		6			
Power Output @ 1800RPM - NG Fuel - HP (kWm)		201 (150)			
Power Output @ 1800RPM - LP Fuel - HP (kWm)		148 (110)			
Aftertreatment Technology		Three Way Catalyst			
Fuel Type & Consumptions (Ft3/Hr)	Natural Gas	1539			
	Propane	517			
FEATURES AND BENEFITS					
Onboard Scrubbing System		Standard			
Dual Fuel (NG / LP)		Standard			
Full Load NG / LP Switching		Standard			
Fuel Source & Pressure Indicator		Standard			
LP Vaporizer		Standard			
Oil Level Maintainer (25 gallons/95 liters)		Standard			
MasterTrak Telematics		Standard			
110% Containment		Standard			
Oversized Air Filtration		Standard			
Running Gear		Standard			
DIMENSIONS WITH RUNNING GEAR					
Length - in (mm)		220.7 (5606)			
Width - in (mm)		82.9 (2105)			
Height - in (mm)		105 (2667)			





## DoosanPortablePower.com | 800.633.5206

© 2018 Doosan Portable Power. All rights reserved.