



Model	XP825/HP750	
COMPRESSOR ROTARY SCREW/SINGLE-STAGE	LO <b>W</b> PRESSURE	HIGH PRESSURE
Free-Air Delivery – cfm (m3/min)	825 (23.4)	750 (21.2)
Rated Operating Pressure – psig (bar)	125 (8.6)	150 (10.3)
Pressure Range – psig (bar)	80-175 (5.5-12.1)	
Air Discharge Outlet Size – in (mm)	2-inch NPT (50.8)	
Air Discharge Outlet Quantity	1	
Fuel Tank Capacity – gal (L)	100 (379)	
ENGINE		
Make/Model	Cummins/QSB6.7	
Emissions Tier Level	Tier 4 Final (T4F)	
Number of Cylinders	6	
Displacement – cu in (L)	408 (6.7)	
Rated Speed – rpm	2100 / 1935	
Idle Speed – rpm	1300	
Bhp @ Rated Speed (kW)	266 (198) / 262 (195)	
Electrical - volts	24	
Hours of Operation @ Full Load	9.1 / 9.3	
DIMENSIONS WITH RUNNING GEAR		
Length – in (mm)	203 (5164)	
Width – in (mm)	90.2 (2291)	
Height – in (mm)	88.5 (2248)	
Track Width – in (mm)	80.3 (2040)	
Tire Size – in	15	
Shipping Weight – w/o fuel – lb (kg)	8620 (3910)	
WorkingWeight – w fuel – lb (kg)	9330 (4230)	
DIMENSIONS WITHOUT RUNNING GEAR		
Length – in (mm)	152.4 (3871)	
Width – in (mm)	80.6 (2047)	
Height – in (mm)	79 (2007)	
Shipping Weight – w/o fuel – lb (kg)	7840 (3560)	
Working Weight – w fuel – lb (kg)	8550 (3880)	

## **Key Features**

- Versatility in application increases productivity and lowers total cost of ownership.
- Sturdy design includes corrosion-resilient galvanneal steel enclosure, A-frame drawbar and heavy-duty axles.
- Thermostatic clutch-driven cooling fan ensures quiet operation and significantly cuts fuel costs. A 100-gallon fuel tank delivers nine hours of reliable runtime.
- State-of-the-art control panel provides improved operator interface and easy-to-understand machine diagnostics.
- Equipped with a Doosan-designed and manufactured airend that offers a highly efficient rotor profile, requiring less horsepower to deliver high-volume cfm output.
- Powered by a high-performance Cummins engine, and engineered with diesel oxidation catalyst (DOC) and selective catalytic reduction (SCR) that is virtually maintenance-free with no regeneration cycles.





## DoosanPortablePower.com | 800.633.5206

## © 2018 Doosan Portable Power. All rights reserved.

Doosan reserves the right to limit quantities, alter lead times or cancel models without prior notice or obligation. Nothing contained in this brochure intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale shall be in accordance with standard Doosan Portable Power terms and conditions of sale for such products, which are available upon request. Specifications in this brochure are subject to change without notice.